LINEAR-6 ELITE (YELLOW)

Technical Specifications

Voltage Range	10-32V
LED Life	50,000 Hours
Weight	495g
HIGH BEAM PERFORMANCE	
Total Luminous Flux	4320 Lm
Total Driver 'FOV' Flux †	2839 Lm
Color Temperature	PC Yellow
Power Consumption	42 Watts
Peak Current Draw	4.07 Amps
Current Draw (at 14.4V)	2.9 Amps
Connector	2-Pin Superseal (+25 cm Cable)
CERTIFICATION	
IP Rating #	IP68
ECE Reference	ECE R10
Salt Spray Test	ISO 9227
Dump Load Protection	ISO 7637-2
DIMENSIONS	
Width	232mm
Depth	62mm
Height	40mm
PHOTOMETRIC DATA	
Horizontal Beam Angle	84° / 18°
0.25Lx Line @	536m
0.5Lx Line @	379m
1Lx Line @	268m
3Lx Line @	155m

† Driver FOV Flux is a measure of effective lumens, taking into consideration the amount of light within a driver's field of view, defined as ±45° left/right and ±10° up/down.

All Lazer products are designed to meet the requirements of IP68 testing. Every lamp produced at our UK facility is fully submerged under water prior to dispatch.